

MODEL		BLAZE 1100-II			BLAZE 1500-II			BLAZE 1800-II			BLAZE 2200-II		
ENJEKSİYON ÜNİTESİ													
VİDA ÇAPI	mm	30	35	40	38	42	45	42	45	50	45	50	55
NET GRAMAJ (PS)	gr	96	149	194	196	252	289	265	326	402	333	447	541
ENJEKSİYON HIZI	gr/sn	60	82	107	100	123	141	129	149	183	136	168	203
ENJEKSİYON BASINCI (MAKS)	bar	2836	2083	1595	2127	1741	1517	2063	1798	1456	2253	1825	1508
KİLİTLEME KUVVETİ	ton	110			150			180			220		
MENGENE STROĞU (MAKS)	mm	340			375			430			490		
KOLONLAR ARASI MESAFE	mm	420 × 370			470 × 420			520 × 470			580 × 530		
KALIP YÜKSEKLİĞİ (min-maks)	mm	150 - 390			160 - 500			180 - 530			200 - 580		
MOTOR GÜCÜ	kw	18.2			18.2			20.4			23		
MAKİNE EBATLARI (U*G*Y)	M	4,4 × 1,2 × 1,6			4,6 × 1,3 × 1,7			5,2 × 1,4 × 1,8			5,9 × 1,6 × 2,0		
MAKİNE AĞIRLIĞI	ton	3.7			4.2			5.3			7.5		

MODEL		BLAZE 2800-II			BLAZE 3500-II			BLAZE 4500-II			BLAZE 5500-II		
ENJEKSİYON ÜNİTESİ													
VİDA ÇAPI	mm	55	60	65	65	70	75	70	75	80	75	85	95
NET GRAMAJ (PS)	gr	584	772	906	981	1226	1407	1226	1508	1715	1689	2169	2709
ENJEKSİYON HIZI	gr/sn	177	211	248	239	278	319	294	337	384	345	443	554
ENJEKSİYON BASINCI (MAKS)	bar	2190	1840	1568	2028	1749	1523	2065	1799	1581	2293	1785	1429
KİLİTLEME KUVVETİ	ton	280			350			450			550		
MENGENE STROĞU (MAKS)	mm	560			670			760			900		
KOLONLAR ARASI MESAFE	mm	630 × 580			730 × 680			780 × 730			886 × 820		
KALIP YÜKSEKLİĞİ (min-maks)	mm	220 - 600			280 - 700			320 - 750			350 - 850		
MOTOR GÜCÜ	kw	28.7			36.7			39.4			55.4		
MAKİNE EBATLARI (U*G*Y)	M	6,7 × 1,8 × 2,0			7,7 × 2,0 × 2,1			8,2 × 2,0 × 2,2			9,1 × 2,2 × 2,2		
MAKİNE AĞIRLIĞI	ton	9.2			13.05			16.3			21.6		

MODEL		BLAZE 7000-II				BLAZE 9000-II				BLAZE 11000-II				BLAZE 13000-II			
ENJEKSİYON ÜNİTESİ																	
VİDA ÇAPI	mm	80	90	100	110	90	100	110	120	100	110	120	130	100	110	120	130
NET GRAMAJ (PS)	gr	2058	2605	3216	3891	2721	3359	4065	4837	3645	4411	5249	6160	3645	4411	5249	6160
ENJEKSİYON HIZI	gr/sn	408	516	637	771	507	625	757	901	626	757	901	1058	626	757	901	1058
ENJEKSİYON BASINCI (MAKS)	bar	2380	1880	1523	1259	2276	1843	1523	1280	2122	1753	1473	1255	2122	1753	1473	1255
KİLİTLEME KUVVETİ	ton	700				900				1100				1300			
MENGENE STROĞU (MAKS)	mm	1000				1130				1230				1320			
KOLONLAR ARASI MESAFE	mm	980 × 960				1080 × 1080				1180 × 1180				1250 × 1250			
KALIP YÜKSEKLİĞİ (min-maks)	mm	400 - 960				450 - 1100				500 - 1200				500 - 1300			
MOTOR GÜCÜ	kw	36.7 + 36.7				39.4 + 39.4				39.4 + 55.4				39.4 + 55.4			
MAKİNE EBATLARI (U*G*Y)	M	10,3 × 2,3 × 2,7				11,2 × 2,5 × 3,3				11,5 × 2,7 × 3,3				12,9 × 2,8 × 3,3			
MAKİNE AĞIRLIĞI	ton	32				45				50				61			